

# 450MT



## POWER

Engine Type	2-Cylinder, Water-Cooled, DOHC
Displacement	449.5cc
Bore×Stroke	72 x 55.2mm
Max Power	32.5kW/8500 rpm
Max Torque	44N·m/6250 rpm
Compression Ratio	11.5:1
Clutch Type	Wet Multi-Plate, Slipper Clutch
Throttle Type	Mechanical Throttle
Emission	International

## DIMENSIONS & WEIGHT

Length x Width x Height	2210×870×1390 mm
Steering Angle	36°
Rake Angle	26°
Trail	106 mm
Wheelbase	1505 mm
Seat Height	820(Standard) / 800(Adjustable) mm
Ground Clearance	220 mm
Fuel Tank Capacity	17.5 L
Dry Weight	175 kg

## CHASSIS/SUSPENSION/BRAKE

Chassis	Steel Tube
Handlebar	One-Piece Tube Variable Diameter Handlebar
Rear Fork	Integrated Aluminum Alloy
Rim	Steel Wire-Spoke Rims (Tubeless)
Front Tire	90/90 -21 CST
Rear Tire	140/70 R18 CST
Front Suspension	φ41 Upside Down Suspension, Hydraulic Damping Adjustable, KYB
Rear Suspension	Central Aligned, Multi-link, Damping Adjustable, KYB
Front/Rear Suspension Stroke	200/200 mm
Front Brake	φ320mm Single Disc, Opposed Four-Piston, J.Juan
Rear Brake	φ240mm Single Disc, Single-Piston, J.Juan
ABS	Standard, BOSCH
TC	Standard, BOSCH

## ELECTRONIC

Key	Mechanical Key
Riding Modes	Standard
Electronic Control Assist	ABS With External Switch (Rear ABS Allows Independent Control)
Battery	12V 11.2Ah
Headlight	LED
Taillight	LED
Turning Light	LED
Instrument	5-inch Curved TFT Screen, OTA, Motoplay
Charging Port	18W USB/Type-C
T-BOX	Optional

## GRAPHIC & TRIM

Zephyr Blue, Tundra Grey

Facebook



Instagram



\*High Front Fender And Three Cases Are Accessories